Table of Contents

1. Product Description 1
2. Dimensions – Pre-Cut Part 2
3. Labelling – Transport Packaging 2
4. Data – Transport Packaging 2
5. Technical Data 2
6. Information about Sealing (Guideline Values) 3
7. Recommended Storage Conditions 3

The technical values represent standard values, in accordance with the usual process variations. They do not release from the obligation of a validation and functional test.

1. Product Description

Medical grade special paper as a test system for the operational qualification (OQ), and for the daily testing, of a sealing device.

Reason for Use

The product can be sealed against PE or PP layers.

Standards

The paper is in accordance with the DIN EN 868 Part 3.

Resistance to Ageing

The products may be used for at least 5 years from date of manufacture when stored suitably (see recommended storage conditions).

hawo GmbH
Obere Au 2-4
74847 Obrigheim / Germany

T + 49 (0) 6261 / 9770-0
F + 49 (0) 6261 / 9770-69
info@hawo.com
www.hawo.com

Entry in the Commercial Register of the Mannheim District Court HRB 441011
Managing Directors: Hans and Christian Wolf
Place of business: Obrigheim

This document and the contents hereof are considered proprietary and confidential information of hawo and disclosure to unauthorized individuals or dissemination, publication, or copying is prohibited without prior written consent by hawo GmbH, 74847 Obrigheim, Germany.

2. Dimensions – Pre-Cut Part

Width	75 mm	/	Tolerance ±1 mm
Length:	175 mm	/	Tolerance ±1 mm

3. Labelling – Transport Packaging

The cartons are marked with a print on the top side and a label on the end. The following information is included:

- Product Description
- Article No.
- Supplier's Batch No.
- Storage Conditions
- Package Contents
- Manufacturer's Address
- Date of Manufacture
- Expiry Date

4. Data – Transport Packaging

Box, white, 350 g/m²

Size: 81 x 185 x 27mm

Print Colours: Red HKS 13 N, Black

Box Contents: 250 sheets

Labelled and sealed in a PE-Film with perforations for opening.

5. Technical Data

Quality Characteristic	Value	Unit
Paper Weight	70 +3/-5	g/m³

hawo GmbH
Obere Au 2-4
74847 Obrigheim / Germany

T + 49 (0) 6261 / 9770-0
F + 49 (0) 6261 / 9770-69
info@hawo.com
www.hawo.com

Entry in the Commercial Register of the Mannheim District Court HRB 441011
Managing Directors: Hans and Christian Wolf
Place of business: Obrigheim

This document and the contents hereof are considered proprietary and confidential information of hawo and disclosure to unauthorized individuals or dissemination, publication, or copying is prohibited without prior written consent by hawo GmbH, 74847 Obrigheim, Germany.

6. Information about Sealing (Guideline Values)

Sealing Temperature	180 - 200°C
Sealing Time:	1,0 - 3,0 sec

7. Recommended Storage Conditions

Temperature: +5°C bis +30°C

Relative Humidity: 35% - 50° RH, store dry

Protect from light and direct lighting.

Only open the outside packaging when the product is to be used.

Do not store near:
- Chemicals
- Cleaning Materials

hawo GmbH
Obere Au 2-4
74847 Obrigheim / Germany

T + 49 (0) 6261 / 9770-0
F + 49 (0) 6261 / 9770-69
info@hawo.com
www.hawo.com

Entry in the Commercial Register of the Mannheim District Court HRB 441011
Managing Directors: Hans and Christian Wolf
Place of business: Obrigheim

This document and the contents hereof are considered proprietary and confidential information of hawo and disclosure to unauthorized individuals or dissemination, publication, or copying is prohibited without prior written consent by hawo GmbH, 74847 Obrigheim, Germany.