

Products Information

Code		Dimensions Detail						
SKG Codes	Aesculap Ref	**A ± 5.00mm**	**B ± 1.00mm**	**C ± 0.50mm**	**D ± 0.50mm**	**E ± 0.25mm**	**F ± 0.25mm**	**Weight**
SKG-2339-16	MA 331	16cm/160mm (6¼")	17.75 mm	10.75 mm	9.25 mm	1.90 mm	2.65 mm	20g ± 3g

Product Description:	Lucae Forceps Serrated
Product Finish:	Satin Finish (As Per Customer Requirement)

Intended use:	Lucae Forceps are specially manufactured as surgical instruments typically used to hold the tissues during surgical procedures.

Material Detail

Product Material:	Stainless steel A.I.S.I 410

Material Specification

Type	Carbon	Manganese	Phosphorus	Sulpher	Chromium	Nickel	Silicon
A.I.S.I 410	0.15% max	1.00% max	0.040% max	0.030% max	11.50 to 13.50	0.12	1.00% max
Furnace Temperature:		900c° - 1100c°		Hardness Standard:		HRC 42 To 45	

Packing Information's

Laser Marking:	CE (As Per Customer Requirement)
Packing:	Single Forceps packed in the single sterile pouch and Dispensing box and outer box
Labeling:	Each Single Pouch is Labeled and Each Dispensing box is Labeled. (As Per Customer Requirement)

Classification:	Class II a Rule 6

Biological Static:	Sterile ☑	Non Sterile ☐		
Sterilization Method:	ETO Sterilization	Shelf Life:	5 Years	

Working Environment		Storage Condition	
Working Temperature:	10°C To 40 °C	Storage Temperature :	10°C To 50 °C
Relative Humidity Range:	≤ RH80 %	Stored in a clean, dry and Moisture Free Area	
Atmospheric Pressure Range:	760hPa - 1060hPa		